

Chevy Tahoe

2007-2014

Install Instructions

Watch for Wires when drilling

1. Install the 11 ½” rear brackets to the cargo barrier facing forward. LOGO also forward, finger tight only. The twisted bracket is on the drivers’ side. Lift the cargo barrier up so the attachment holes in the end of the brackets are just above the pillar post plastic. *Keep the barrier to the rear to allow the seats to go forward and lock back. Just touching the headrests is good.* Make a mark on the headliner, just above the plastic on each side.
2. Remove the plastic from the rear Pillar posts. Use caution not to lose the small attaching screw. Center the 2 1/2” Bracket on the passenger side and the 1 1/2” bracket on the drivers’ side. **See 'PHOTO'**, Attach by using two 1 1/2” tap screw for each bracket. The brackets will tuck under the headliner leaving ¼” exposed and fasten with tap screws.
3. Replace “Pillar Post” plastic. Insure the brackets align with the marks on the headliner. Drill a small pilot hole through your marks.
4. Hold cargo barrier in position and attach through the holes you just drilled.
5. With the passenger seat fully forward, place the side screen between the rear seats. Attach to the rear cargo barrier.
6. Install the upper and lower bracket to the front screen, **SEE PHOTO**, with the brackets facing forward. Install the foam tube, to the upper front partition with zip ties.
7. Install the front screen to the side screen. Install upper front screen behind the seatbelt carrier. May have to adjust up and down to lessen the gap at the ceiling.
8. Install the screened floor bracket to the side and front screen. Tighten these three bolts. Pull the front screen towards the passenger side pillar post and fasten to the Seatbelt bolt. Fasten the lower right bracket to the floor with a tap screw, **if you feel it’s necessary.**
9. Tighten all bolts and then tap screw the screened floor bracket to the floor pan, **again if you feel its necessary**
10. Finish foam tube.

**Chevy Tahoe
2007-2014
Install Instructions**

